

PPG

SAND FILTER FILTRE À SABLE ZANDFILTER



 **PPG Laminated Polyester Filter**

 **PPG Filtre Polyester Laminé**

 **Gelaagde Polyester Filter**

PPG

SAND FILTER FILTRE À SABLE ZANDFILTER



Characteristics

- Laminated polyester, reinforced with fiberglass
- Collector with 8 laterals (16 for diam. 900 mm)
- 6 way manual valve
- Manometer
- Airbleed
- Large diameter, transparent cover
- Drain
- Working pressure 2,5 bar - test 3,75 bar
- Warranty 7 years

Caractéristiques

- Polyester laminé, renforcé de fibres de verre
- Collecteur à 8 bras (16 pour diam. 900 mm)
- Vanne 6 positions
- Manomètre
- Purge d'air
- Couvercle extra grand, transparent
- Bouchon de vidange
- Pression de travail 2,5 bar - test 3,75 bar
- Garantie 7 ans

Eigenschappen

- Glasvezel versterkte gelaagde polyester
- Collector met 8 armen (16 voor 900 mm)
- 6 weg-klep
- Manometer
- Ontluchter
- Extra groot transparant deksel
- Leeglaatstop
- Werkdruk 2.5 bar – test 3.75 bar
- Garantie 7 jaar

Range - Gamme - Gamma

Diam.	m ³ /h max	Conn.	Sand / Sable / Zand	Silex	H	Diam. incl valve/vanne/klep
560 mm	10	1 1/2"	75 kg	25 kg	855 mm	810 mm
640 mm	15	1 1/2"	100 kg	50 kg	930 mm	930 mm
760 mm	22	2"	175 kg	50 kg	1070 mm	1090 mm
900 mm	13	2"	250 kg	75 kg	1095 mm	1230 mm


POLLET POOL GROUP

